
BUMPER QUALITY LABEL

THIS VEHICLE IS EQUIPPED WITH A BUMPER SYSTEM THAT CAN WITHSTAND A FRONTAL BARRIER IMPACT SPEED OF 2.5 MILES PER HOUR AND A REAR IMPACT SPEED OF 2.5 MILES PER HOUR WITH NO MORE DAMAGE THAN ALLOWED BY THE FEDERAL BUMPER STANDARD. THE FEDERAL BUMPER STANDARD ALLOWS DAMAGE TO THE BUMPERS AND ATTACHING HARDWARE AND SPECIFIES BARRIER TESTS TO BE CONDUCTED AT 2.5 MILES PER HOUR.

PARTS CONTENT INFORMATION

FOR VEHICLES IN THIS CARLINE U.S./ CANADIAN PARTS CONTENT **60%**

Note Part Content Does Not Include Final Assembly, Distribution, Or Other Non-parts Costs

FOR THIS VEHICLE FINAL ASSEMBLY POINT
FLAT ROCK , MICHIGAN
U.S.

COUNTRY OF ORIGIN:

ENGINE: **U.S.**

TRANSMISSION: **MEXICO**



1FATP8JZ1G5525642

TO BE REMOVED
BY THE CUSTOMER ONLY